



### Technical Specifications

## HP ProDisplay P200 19.5-inch LED Backlit Monitor



1. Menu: Opens, selects or exits the OSD menu.
2. "-": If the OSD menu is on, press to navigate backward through the OSD menu and decrease adjustment levels.
3. "+"/Input: Select input source. If the OSD menu is on, press to navigate forward through the OSD menu and increase adjustment levels.
4. OK/auto: If the OSD menu is on, press to select the highlighted menu item. If the OSD menu is inactive, press to activate the auto adjustment feature to optimize the screen image.
5. Power/Power LED  
fully powered = green; sleep mode = amber; sleep timer mode = flashing amber.



(Multi-monitor support depends on your PC capability.  
Monitors and stands sold separately)

Use two HP ProDisplay P200 monitors combined with an HP Adjustable Dual Display Stand (AW664AA) for a small footprint, high productivity work solution.

### Technical Specifications

## Overview

### Introduction

Save money and be more productive with a business monitor that delivers solid performance, proven HP quality and reliability, a stable lifecycle, HP accessory compatibility, and energy savings at a very attractive price point.

### Key Benefits

- Enjoy quality front-of-screen performance for all of your daily tasks.
- Get a stable product lifecycle and minimum one-year lifespan at a price point that's easy on your wallet.
- Reduce power consumption and help lower your costs with an energy-efficient design.
- Get ample room for your essential tasks on the 19.5-inch diagonal screen with a small footprint that leaves plenty of room on the desk.
- Design a multiple monitor workspace that puts everything you need front and center.<sup>7</sup>
- Add audio, mount the display on a wall or create a compact PC/display configuration.<sup>2</sup>
- Design the screen for how you work with HP Display Assistant software.
- Get award-winning service and support by phone or online.

### Models

**Part Number:** F7M92AA

<b>Panel</b>	<b>Type</b>	TN (Twisted Nematic) LED Backlit LCD
	<b>Viewable Image Area (diagonal)</b>	<b>49,53 cm (19.5 in)</b> widescreen, diagonally measured
	<b>Active Area (W x H)</b>	<b>43,3 x 23,6 cm (17.04 x 9.29 in); ± 3 mm</b>
	<b>Aspect Ratio</b>	16:9
	<b>Viewing Angle (typical)*</b>	Up to 170° horizontal/160° vertical (10:1 minimum contrast ratio)
	<b>Brightness (typical)*</b>	250 nits (cd/m <sup>2</sup> )
	<b>Dynamic Contrast Ratio (typical)</b>	1000:1
	<b>Contrast Ratio (typical)*</b>	3,000,000:1
	<b>Response Time (typical)*</b>	5 ms (On/Off)
	<b>Pixel Pitch</b>	0.269 mm
	<b>Backlight Lamp Life (to half brightness)</b>	30,000 hours minimum
	<b>Color Gamut</b>	72%
	<b>Color Support**</b>	Can display up to 16.7 million colors
	* All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.	
	** With the use of FRC technology.	
<b>On Screen Display (OSD)</b>	<b>Buttons or Switches</b>	Menu, Minus ("−"), Plus ("+") /Input Control, OK/Auto, Power

### Technical Specifications

	<b>Languages</b>	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)	
	<b>User Controls</b>	Brightness, Contrast, Color, Image Control, OSD control, Management, Language, Information, Factory Reset, Input Control	
<b>Video/Other Inputs</b>	<b>Plug and Play</b>	Yes	
	<b>Input Connectors</b>	(1) 15-pin mini D-sub analog VGA and (1) DVI-D; HDCP support on DVI input	
	<b>Video Cables</b>	VGA, DVI-D	
	<b>Video Cable Length</b>	<b>1,8 m</b> (5.9 ft); detached	
<b>Signal Interface/ Performance</b>	<b>USB</b>	N/A	
	<b>Horizontal Frequency</b>	24 to 70 kHz	
	<b>Vertical Frequency</b>	50 to 60 Hz	
	<b>Native Resolution</b>	1600 x 900 @ 60 Hz	
	<b>Max Resolution (Digital)</b>	1600 x 900 @ 60 Hz	
	<b>Preset VESA Modes (non-interlaced)</b>	640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz	
	<b>Max Pixel Clock Speed</b>	170 MHz	
	<b>User Programmable Modes</b>	Yes, 10	
	<b>Anti-Glare</b>	Yes	
	<b>Anti-Static</b>	Yes	
	<b>Default Color Temperature</b>	Warm (6500° Kelvin)	
<b>Power</b>	<b>Power Supply</b>	Internal	
	<b>Input Power</b>	90 - 265 VAC at 45 - 63 Hz	
	<b>Typical Power Consumption</b>	18 W	
	<b>Maximum</b>	22 W	
	<b>Power Saving</b>	0.5 W	
	<b>Power Cable Length</b>	<b>1,9 m</b> (6.2 ft)	
<b>Mechanical</b>	<b>Dimensions (W x D x H)</b>	<b>Unpacked w/stand</b>	<b>46,7 x 15,21 x 34,53 cm</b> (18.39 x 5.99 x 13.59 in)
		<b>Unpacked w/o stand (head only)</b>	<b>46,7 x 5,1 x 28,08 cm</b> (18.39 x 2.01 x 11.06 in)

### Technical Specifications

	<b>Packaged</b>	<b>53,2 x 13,5 x 36,1 cm</b> (20.94 x 5.31 x 14.21 in)	
	<b>Base area (footprint)</b>	<b>15,44 x 15,21 cm</b> (6.08 x 5.99 in)	
<b>Weight</b>	<b>Head Only</b>	<b>2,37 kg</b> (5.22 lb)	
	<b>Unpacked</b>	<b>2,85 kg</b> (6.28 lb)	
	<b>Packaged</b>	<b>4,06 kg</b> (8.94 lb)	
<b>Tilt Range</b>	-5° to +25°		
<b>Swivel Range</b>	N/A		
<b>Height Adjustable</b>	N/A		
<b>Pivot Rotation</b>	N/A		
<b>Base</b>	Detachable		
<b>Environmental</b>	<b>Temp. – Operating</b>	41° to 95° F (5° to 35° C)	
	<b>Temp. – Non-operating</b>	-4° to 140° F (-20° to 60° C)	
	<b>Humidity – Operating</b>	20% to 80%, non-condensing	
	<b>Humidity – Non-operating</b>	5% to 95%	
	<b>Altitude – Operating</b>	<b>0 to 5000 m</b> (0 to 16,404 ft)	
	<b>Altitude – Non-operating</b>	<b>0 to 12192 m</b> (0 to 40,000 ft)	
	<b>White LED Backlights</b>	Yes	
	<b>CCFL Panel</b>	No	
	<b>Arsenic-Free Display Glass</b>	Yes	
	<b>Low Halogen<sup>4</sup></b>	Yes, except external cables	
	<b>Mercury-Free Display Backlighting</b>	Yes	
	<b>Options</b>	<b>HP LCD Speaker Bar</b> — Part number NQ576AA	Powered directly by the connected PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors. Features include dual speakers with full sound range and dual external headphone jacks. Sold separately. For more information, refer to the product's QuickSpecs.
		<b>HP LCD Monitor Quick Release</b> —Part number EM870AA <sup>1</sup>	An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document.
<b>HP Integrated Work Center Stand for Small Form Factors v3</b> — Part number F2P06AA <sup>5</sup>		Maximize your available work space with the stylish and innovative HP Integrated Work Center for Small Form Factors v3 (HP IWC SFF v3), designed to match the newest HP PC designs. Create a customized "all-in-one" solution by combining an HP Small Form Factor (SFF) Business Desktop PC or Workstation with an LED monitor up to 24 diagonal inches.	
<b>HP Integrated Work Center Stand - USDT / Thin Clients</b> — Part numbers		HP Integrated Work Center Stand - USDT / Thin Clients - The HP Integrated Work Center Stand is designed to help maximize the use of limited desk space without compromising performance or productivity by accommodating an HP Ultra-slim	

### Technical Specifications

<p>E8H16AA/AT (black and meteorite), LH526AA/AT (black and silver).<sup>6</sup></p> <p><b>HP Adjustable Dual Display Stand</b> — Part Number AW664AA</p> <p><b>HP Display and Notebook II Stand</b> — Part number E8G00AA</p> <p><b>HP Adjustable Display Stand</b> — Part number AW663AA</p> <p><b>HP USB Graphics Adapter</b> — Part number NL571AA</p> <p><b>HP Dual Output USB Graphics Adapter</b> — Part Number C5U89AA</p> <p><b>HP Business PC Security Lock Kit</b> — Part number PV606AA</p> <p><b>HP DVI to DVI cable</b> — Part number DC198A</p>	<p>Desktop PC or an HP Thin Client, and most HP 17 to 24-inch<sup>1</sup> diagonal LCD monitors, with VESA standard mounting brackets.</p> <p>Premium space-saving dual screen solution provides access to more monitor real estate and makes it possible to manage multiple applications simultaneously. Weight adjustable for dual monitors from 17-24". Rotate displays into portrait/landscape positions.</p> <p>Quickly and easily create a comfortable workspace for your notebook or notebook and docking station and an external display with the HP Display and Notebook II Stand, which brings your notebook PC, docking station, and display up off the desk.</p> <p>Turn your HP Business Notebook into a desktop solution supporting up to a 24 inch display. A dual-hinged, smooth-motion display stand allows for greater depth, height and tilt adjustment for maximum comfort.</p> <p>Enables connection of up to six simultaneous displays to help you boost productivity and multi-task across several open applications. Use one Adapter to bridge between a notebook or desktop PC and second monitor or use multiple Adapters to connect several displays to each other.</p> <p>You can boost your productivity by creating a dual-monitor setup with the HP Dual Output USB Graphics Adapter – featuring both DVI-I and DisplayPort inputs to drive displays at high resolutions through a single USB 3.0 connection to your PC.</p> <p>Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point.</p> <p>Connect to external monitors with a DVI connector from an HP Compaq Business Desktop computer with a DVI connector. The cable is a single link cable with DVI-D support on both connectors. The cable will connect to either a DVI-D or DVI-I connector on the monitor and the graphics card.</p>
---	--

<b>What's in the box?</b>	<p><b>Monitor and Accessories</b> HP ProDisplay P200 19.5-inch LED Backlit Monitor; AC power cord (1.9m) 6.2 ft; VGA cable (1.8m) 5.9 ft; DVI cable (1.8m) 5.9 ft</p> <p><b>Documentation</b> CD (includes user guide, warranty, drivers)</p> <p><b>Featured Software</b> Yes, HP Display Assistant</p>
<b>Other</b>	<p><b>User Guide Languages</b> English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.</p> <p><b>Warranty Languages</b> English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.</p> <p><b>Color</b> Black</p> <p><b>VESA External Mounting</b> Yes (one set of standard 4-hole pattern, 100 mm). Base must first be removed.</p> <p><b>Security Lock-Ready</b> Yes</p>

### Technical Specifications

<b>Certification and Compliance</b>	CE, CB, KC, KCC, NOM, PSB, ICE, TUV-S, CCC, CEL Grade 1, CECP, SEPA, EPA, ISC, VCCI, FCC, Taiwan: BSMI, SmartWay Transport Partnership - NA only, Microsoft WHQL Certification Windows 8 and Windows 7, ENERGY STAR®, EPEAT® Gold (select regions) <sup>3</sup> .
<b>Compatibility</b>	VESA Video Signal Standard (VSI) Compliant video cards have been tested and proven compatible for use with this monitor. Recommended for use with HP products.
<b>Service and Warranty</b>	Protected by HP, including a 3 year standard limited warranty. Select HP Care Pack Services <sup>2</sup> to extend service contracts beyond the standard warranties.

1. The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) for all devices mounted. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.

2. HP Care Pack Services extend service contracts beyond the standard warranties. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at <http://www.hp.com/go/lookuptool>. Additional HP Care Pack Services information by product is available at <http://www.hp.com/hps/carepack>.

3. EPEAT® Gold registered models of this product are available where HP registers commercial display products. See [www.epeat.net](http://www.epeat.net) for registration status in your country.

4. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

5. 17 to 24-inch diagonal monitors need to meet supported weight limits of 6 to 12.1 lbs. (2.7 to 5.5 kg).

6. The Integrated Work Center Stand has been designed to support 17 to 24-inch diagonal HP LCD monitors from 2.3 kg to 5.2 kg (5.07 lbs to 11.24 lbs).

7. Each accessory sold separately. Mounting hardware sold separately.

© Copyright 2014 Hewlett-Packard Development Company, L.P. All rights reserved.

ENERGY STAR is a registered mark owned by the U.S. government. All other product names mentioned herein may be trademarks of their respective companies.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

